

## Roulement à aiguilles RNA4917-U-IKO - RNA4917-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/rna4917-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)
100	---	<b>RNA 4917U</b>	---	---	695	100	120	35	1.1
Standard rounding dimension $D_s$ Max. mm									
	Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed(2) rpm						
113.5	103 000	225 000	1 900						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379739
Diam. intérieur	100 mm
Diam. extérieur	120 mm
Épaisseur	35 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE