

Roulement à aiguilles RNA6917-UU-IKO - RNA6917-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/rna6917-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
100	—	—	RNA 6917UU	—	1 300	100	120	63	1.1
Standard mounting dimension D_s Max. mm									
	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed (2) rpm						
	113.5	168 000	448 000	1 900					

Notes (1) Minimum allowable value of chamfer dimension r_s .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379753
Diam. intérieur	100 mm
Diam. intérieur	3.937" inch
Diam. extérieur	120 mm
Diam. extérieur	4.724" inch
Epaisseur	63 mm
Epaisseur	2.48" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE