

Roulement à aiguilles RNA4920-U-IKO - RNA4920-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/rna4920-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|---|--|---|--|---------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_a (1) |
| 115 | — | RNA 4920U | — | — | 1 200 | 115 | 140 | 40 | 1.1 |
| Standard rounding dimension D_s Max. mm | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed(2) rpm | | | | | | |
| 133.5 | 134 000 | 297 000 | 1 700 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952379852 |
| Diam. intérieur | 115 mm |
| Diam. extérieur | 140 mm |
| Épaisseur | 40 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE