


Roulement à rouleaux NNTR65X160X75-2ZL-INA - NNTR65X160X75-2ZL-INA

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nntr65x160x75-2zl-ina>

Yoke type track rollers NNTR65X160X75-2ZL
Full complement roller set, axial guidance, central rib, sealing shields with lamellar ring on both sides



d	65 mm
D	160 mm Tolerance: h10
B	75 mm
C	3 Number of lubrication holes
C	73 mm
D ₁	103 mm
d ₂	82 mm
d ₃	5 mm
R	10000 mm Curvature radius
r ₁	2 mm
r ₂	3 mm
m	8,8 kg Mass
C _{dyn}	285000 N Effective dynamic load rating as track roller (radial)
C _{st}	395000 N Effective static load rating as track roller (radial)
F _{dyn}	350000 N Permissible dynamic radial load
F _{st}	395000 N Permissible static radial load
C _{fat}	50000 N Fatigue limit load
n	700 1/min Speed (with continuous operation and grease lubrication)

CARACTÉRISTIQUES PRODUIT

Marque	INA
N° Ean13	4047643241250
Diam. intérieur	65 mm
Diam. extérieur	160 mm
Épaisseur	75 mm
Poids	8850 g
Charge dynamique	270 kN
Charge statique	400 kN
Conditionnement	-
Norme	-

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE