

Roulement à aiguilles NA6901-U-IKO - NA6901-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na6901-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
12	—	—	—	—	NA 6901U	45.5	12	24	22	23

r_s min (1)	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 121623
		Min.	Max.	Max.				
0.3	16	14	15	22	15 500	20 400	12 000	

Notes: (1) Minimum allowable value of shaft diameter r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381107
Diam. intérieur	12 mm
Diam. extérieur	24 mm
Épaisseur	23 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE