

Roulement à aiguilles NA4902-U-IKO - NA4902-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4902-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
15	—	NA 4902U	—	—	36	15	28	13	14

r _s min ⁽¹⁾	F _w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		d _s Min.	d _s Max.					
0.3	20	17	19	26	9 570	11 600	9 500	LRTZ 152014

Notes: (1) Minimum allowable value of shaft dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381121
Diam. intérieur	15 mm
Diam. intérieur	0.591" inch
Diam. extérieur	28 mm
Diam. extérieur	1.102" inch
Epaisseur	14 mm
Epaisseur	0.551" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE