

Roulement à aiguilles NA4903-U-IKO - NA4903-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4903-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
17	—	NA 4903U	—	—	39.5	17	30	13	14

r_s min	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRTZ 172214
		Min.	Max.	Max.				
0.3	22	19	21	28	10 300	13 100	8 500	

Notes: (1) Minimum allowable value of shaft diameter r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381176
Diam. intérieur	17 mm
Diam. extérieur	30 mm
Épaisseur	14 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE