

## Roulement à aiguilles NA4905-U-IKO - NA4905-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4905-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
25	—	NA 4905U	—	—	92.5	25	42	17	18

  

$r_s$ min (1)	$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed(2) rpm	Assembled inner ring LRTZ 253018
		Min.	Max.	$d_s$ Max.				
0.3	30	27	29	40	20 300	25 100	6 500	

Notes(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381305
Diam. intérieur	25 mm
Diam. extérieur	42 mm
Épaisseur	17 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE