

Roulement à aiguilles NA4906-U-IKO - NA4906-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4906-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
30	—	NA 4906U	—	—	106	30	47	17	18

r_s min (1)	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 303518
		Min.	Max.	Max.				
0.3	35	32	34	45	21 500	28 400	5 500	

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381381
Diam. intérieur	30 mm
Diam. extérieur	47 mm
Épaisseur	18 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE