

## Roulement à aiguilles NA6906-U-IKO - NA6906-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na6906-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
30	—	—	—	—	NA 6906U	185	30	47	30	31

  

$r_s$ min (1)	$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed(2) rpm	Assembled inner ring
		Min.	Max.	Max.				
0.3	35	32	34	45	40 100	63 000	5 500	LRTZ 303531

Notes(1)  
(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381398
Diam. intérieur	30 mm
Diam. extérieur	47 mm
Épaisseur	31 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE