

Roulement à aiguilles
NA49-32-U-IKO - NA49-32-U-IKO

https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na49-32-u-iko



MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
32	—	NA 49/32U	—	—	167	32	52	20	21

r _s mm (1)	F _N	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		d _s Min.	D _s Max.					
0.6	40	36	39	48	29 400	44 200	5 000	LRTZ 324021

Notes (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381428
Diam. intérieur	32 mm
Diam. extérieur	52 mm
Epaisseur	21 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE