

## Roulement à aiguilles NA6912-U-IKO - NA6912-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na6912-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$g$	$d$	$D$	$C$
<b>60</b>	—	—	—	<b>NA 6912U</b>	785	60	85	45	46
$r_s$ min	Standard mounting dimensions (mm)		Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring			
1	68	65 66 80	N 93 400	N 186 000	rpm 3 000	LRTZ 608846			

Notes: (1) Minimum allowable value of shaft diameter  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381671
Diam. intérieur	60 mm
Diam. extérieur	85 mm
Épaisseur	46 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE