

## Roulement à aiguilles NA4914-U-IKO - NA4914-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4914-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
70	—	NA 4914U	—	—	770	70	100	30	31

r <sub>s</sub> min <sup>(1)</sup>	F <sub>w</sub>	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.				
1	80	75	78	95	76 900	143 000	2 500	LRTZ 708031

Notes: (1) Minimum allowable value of shaft diameter r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381749
Diam. intérieur	70 mm
Diam. intérieur	2.756" inch
Diam. extérieur	100 mm
Diam. extérieur	3.937" inch
Epaisseur	31 mm
Epaisseur	1.22" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE