

## Roulement à aiguilles NA4915-U-IKO - NA4915-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4915-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
<b>75</b>	—	<b>NA 4915U</b>	—	—	815	75	105	30	31

  

$r_s$ min	$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
		Min.	Max.	Max.				
1	85	80	83	100	79 600	153 000	2 000	LRTZ 758531

Notes: (1) Minimum allowable value of shaft diameter  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381787
Diam. intérieur	75 mm
Diam. extérieur	105 mm
Épaisseur	31 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE