

Roulement à aiguilles NA4917-UU-IKO - NA4917-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4917-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|------------------|-----------------------|---------------|----------------|---------------|---------------------|---------------------------|-----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B |
| 85 | NA 4917UU | | | | 1 300 | 85 | 120 | 35 | 36 |

| r_s min | F_w | Standard mounting dimensions (mm) | | Basic dynamic load rating C | Basic static load rating C_0 | Allowable rotational speed ⁽¹⁾ rpm | Assembled inner ring | |
|-----------|-------|-----------------------------------|------|--------------------------------|-----------------------------------|--|----------------------|--------------|
| | | Min. | Max. | | | | | |
| 1.1 | 100 | 91.5 | 98 | 113.5 | 103 000 | 225 000 | 1 900 | LRTZ 8510036 |

Notes:
(1) Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
1. This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952381855 |
| Diam. intérieur | 85 mm |
| Diam. extérieur | 120 mm |
| Épaisseur | 36 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE