

## Roulement à aiguilles NA4918-UU-IKO - NA4918-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4918-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
90	NA 4918UU				1 360	90	125	35	36

$r_s$ mm	$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring LRTZ 9010536
		$d_s$ Min.	$d_s$ Max.				
1.1	105	96.5	103	118.5	106 000	238 000	1 800

Notes:  
(1) Minimum allowable value of outer diameter  $r$   
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381893
Diam. intérieur	90 mm
Diam. extérieur	125 mm
Épaisseur	36 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE