

Roulement à aiguilles NA4918-U-IKO - NA4918-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4918-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
90	—	NA 4918U	—	—	1 360	90	125	35	36

r_s min (1)	F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min.	Max.					
1.1	105	96.5	103	118.5	106 000	238 000	1 800	LRTZ 9010536

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381909
Diam. intérieur	90 mm
Diam. extérieur	125 mm
Épaisseur	36 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE