

Roulement à aiguilles NA6918-UU-IKO - NA6918-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na6918-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
90	—	—	NA 6918UU	—	2 480	90	125	63	64

r_s mm	F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		d_s Min.	D_s Max.					
1.1	105	96.5	103	118.5	172 000	471 000	1 800	LRTZ 9010564

Notes⁽¹⁾ Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381923
Diam. intérieur	90 mm
Diam. extérieur	125 mm
Épaisseur	64 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE