

## Roulement à aiguilles BR142216-U-IKO - BR142216-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/br142216-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>22.225</b> ( $\frac{7}{8}$ )		<b>BR 142216 U</b>	76	22.225 ( $\frac{7}{8}$ )	34.925 (1 $\frac{3}{8}$ )	25.400 (1 )
Standard mounting dimensions mm		Basic dynamic load rating $C_0$	Basic static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_4$ Max.	$F_{a \text{ max}}$ <sup>(†)</sup>	N	N	rpm		
29.7	1.0	21 600	26 900	9 000		

Notes: (\*) Minimum allowable value of chamfer dimension r.  
(†) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382135
Diam. intérieur	22.225 mm
Diam. extérieur	34.925 mm
Épaisseur	25.4 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE