


Roulement à aiguilles BR486028-U-IKO - BR486028-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/br486028-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
76.200 (3)		BR 486028 U	585	76.200 (3)	95.250 (3 7/8)	44.450 (1 7/8)
Standard mounting dimensions mm		Basic dynamic load rating C_0	Basic static load rating C_0	Allowable rotational speed ^(*)		
D_1 Max.	F_{is} max (⁽¹⁾)	N	N	rpm		
87.0	2.0	105 000	211 000	2 500		

Note⁽¹⁾: Minimum allowable value of chamfer dimension r
^(*): Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382388
Diam. intérieur	76.2 mm
Diam. extérieur	95.25 mm
Épaisseur	44.45 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE