

Roulement à aiguilles BRI142620-UU-IKO - BRI142620-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bri142620-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
22.225 ($\frac{7}{8}$)	BRI 142620 UU		177	22.225 ($\frac{7}{8}$)	41.275 ($1\frac{3}{4}$)	31.750 ($1\frac{1}{4}$)	32.000
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 141820 B
	Min.	Max.	$r_{as\ max}$ ⁽¹⁾				
28.575 ($1\frac{1}{4}$)	27	27.5	36.0	0.6	34 900	49 900	7 000

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382548
Diam. intérieur	22.225 mm
Diam. extérieur	41.275 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE