

Roulement à aiguilles BRI243720-UU-IKO - BRI243720-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bri243720-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		g	d	D	C	B
38.100 (1 1/2)	BRI 243720 UU		293	38.100 (1 1/2)	58.738 (2 3/4)	31.750 (1 1/4)	32.000	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
	Min.	Max.	$r_{as max}$ ⁽¹⁾					
44.450 (1 3/4)	43.3	43.4	51.5	0.6	47 500	78 200	4 500	LRBZ 242820 B

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382654
Diam. intérieur	38.1 mm
Diam. extérieur	58.738 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE