


## Roulement à aiguilles BRI325228-U-IKO - BRI325228-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bri325228-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		$g$	$d$	$D$	$C$
50.800 (2)		<b>BRI 325228 U</b>	889	50.800 (2)	82.550 (3 $\frac{1}{4}$ )	44.450 (1 $\frac{3}{4}$ )	44.700
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring <b>LRBZ 324028 B</b>
	Min.	Max.	$r_{as max}$ <sup>(*)</sup>				
63.500 (2 $\frac{1}{2}$ )	58	61	74.3	1.5	94 600	174 000	3 000

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382722
Diam. intérieur	50.8 mm
Diam. extérieur	82.55 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE