

## Roulement à aiguilles BRI406028-U-IKO - BRI406028-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bri406028-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		$g$	$d$	$D$	$C$
<b>63.500</b> (2 1/2)		<b>BRI 406028 U</b>	1 065	63.500 (2 1/2)	95.250 (3 7/8)	44.450 (1 3/4)	44.700
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
	Min.	Max.				$r$	$r_{as max}$
76.200 (3 )	71	73	105 000	211 000	2 500	LRBZ 404828 B	

Notes:  
(1) Minimum allowable value of chamfer dimension  $r$   
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382760
Diam. intérieur	63.5 mm
Diam. extérieur	95.25 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE