

Roulement à aiguilles GBR101816-U-IKO - GBR101816-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbr101816-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
15.875 ($\frac{5}{8}$)	GBR 101816 UU		69.5	15.875 ($\frac{5}{8}$)	28.575 (1 $\frac{1}{8}$)	25.400 (1)
Standard mounting dimensions mm		Ball dynamic load rating C_0	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A Max.	r as max (^(†))	N	N	rpm		
24.5	0.6	23 500	28 500	5 000		

Notes: (*) Minimum allowable value of diameter dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382845
Diam. intérieur	15.875 mm
Diam. intérieur	5/8" inch
Diam. extérieur	28.575 mm
Diam. extérieur	1 1/8" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE