


## Roulement à aiguilles GBR223020-U-IKO - GBR223020-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbr223020-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>34.925</b> (1 3/8)	<b>GBR 223020 UU</b>		183	34.925 (1 3/8)	47.625 (1 7/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Ball dynamic load rating $C_0$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$	$r_{as}$ max	N	N	rpm		
42.8	0.6	49 500	91 800	2 500		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382975
Diam. intérieur	34.925 mm
Diam. intérieur	1 3/8" inch
Diam. extérieur	47.625 mm
Diam. extérieur	1 7/8" inch
Epaisseur	31.75 mm
Epaisseur	1 1/4" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE