

## Roulement à aiguilles GBR364828-U-IKO - GBR364828-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbr364828-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>57.150</b> (2 1/4)	<b>GBR 364828 U</b>		515	57.150 (2 1/4)	76.200 (3 )	44.450 (1 3/4)
Standard mounting dimensions mm		Ball dynamic load rating $C_1$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$	$r$ as max	N	N	rpm		
69.2	1.5	87 500	161 000	1 400		

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383101
Diam. intérieur	57.15 mm
Diam. extérieur	76.2 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE