


Roulement à aiguilles GBR405228-UU-IKO - GBR405228-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbr405228-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
63.500 (2 1/2)	GBR 405228 UU		560	63.500 (2 1/2)	82.550 (3 1/4)	44.450 (1 3/4)
Standard mounting dimensions mm		Ball dynamic load rating C_0	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A	r as max	N	N	rpm		
75.7	1.5	93 300	179 000	1 300		

Notes: (*) Minimum allowable value of chamfer dimension r
(*) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383125
Diam. intérieur	63.5 mm
Diam. extérieur	82.55 mm
Épaisseur	44.45 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE