

## Roulement à aiguilles NAFW355034-IKO - NAW355034-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/naw355034-iko>

**IKO**  
**NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE**  
With Inner Ring

Shaft dia. mm	Identification number	Mess (Ref.) g	Boundary dimensions mm					Standard mounting dimensions mm				
			d	D	C	r <sub>s</sub> min	F <sub>w</sub>	d <sub>b</sub> Max.	D <sub>b</sub> Min.	d <sub>4</sub> Max.	D <sub>4</sub> Max.	
35	NAFW 355034	230	35	50	34	0.3	40	43.5	48	37	39	40.8
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring									
N	N	rpm	LRT 354034									
38 000	85 400	12 000										

Notes:  
① Minimum allowable value of chamber dimension r  
② Allowable rotational speed applies to grease lubrication.  
Remark:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952384641
Diam. intérieur	35 mm
Diam. extérieur	55 mm
Épaisseur	34 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE