


Roulement à aiguilles NAU4905-UU-IKO - NAU4905-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nau4905-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾	J
25	—	NAU 4905UU	89	25	42	17	0.3	29.5
E _w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
	N	N	rpm					
37	11 900	13 900	6 500					

Notes^(*)
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952385938
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	42 mm
Diam. extérieur	1.654" inch
Epaisseur	17 mm
Epaisseur	0.669" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE