


Roulement à aiguilles NAU4928-IKO - NAU4928-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nau4928-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings



NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ r _{s min}	J	E _w
140	—	NAU 4928	3 840	140	190	50	2	157.5	176
Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm							
174 000	327 000	2 500							

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386072
Diam. intérieur	140 mm
Diam. intérieur	5.512" inch
Diam. extérieur	190 mm
Diam. extérieur	7.48" inch
Epaisseur	50 mm
Epaisseur	1.969" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE