


## Roulement à aiguilles NAU4915-UU-IKO - NAU4915-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nau4915-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings [With Seal]  
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> min	J
75	—	NAU 4915UU	750	75	105	30	1	83.5
E <sub>w</sub>	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
	N	N	rpm					
	95.5	54 800	88 200	2 500				

Notes<sup>(\*)</sup>  
(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAU and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386317
Diam. intérieur	75 mm
Diam. extérieur	105 mm
Épaisseur	30 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE