


## Roulement à aiguilles NAG4920-UU-IKO - NAG4920-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nag4920-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings **[With Seal]**  
Full Complement Roller Bearings **[With Seal]**



NAG49-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r <sup>(1)</sup>	J
100	<b>NAG 4920UU</b>	—	—	1 850	100	140	40	1.5	114.5
E <sub>w</sub>	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>						
	N	N	rpm						
	129.5	152 000	292 000	1 200					

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386577
Diam. intérieur	100 mm
Diam. extérieur	140 mm
Épaisseur	40 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE