

Roulement à aiguilles NAS5013-UU-NR-IKO - NAS5013-UU-NR-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nas5013-uu-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
65	NAS 5013UUNR		1.30	65	100	104.8	46	45	34	5.5
<i>f</i>	<i>c</i>	<i>r</i> mm ⁽¹⁾	<i>J</i>	Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm				
2.5	2	0.6	78	128 000	224 000	1 600				

Notes⁽¹⁾ Minimum allowable value of chamfer dimension *r*
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386843
Diam. intérieur	65 mm
Diam. extérieur	100 mm
Épaisseur	46 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE