


## Roulement à aiguilles NAS5026-UU-NR-IKO - NAS5026-UU-NR-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nas5026-uu-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
130	NAS 5026UUNR		10.5	130	200	208.4	95	94	77	8.5

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C <sub>r</sub> N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
3	3	1	156	537 000	1 000 000	750

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952387024
Diam. intérieur	130 mm
Diam. extérieur	200 mm
Épaisseur	95 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE