

Roulement à aiguilles NBX6040Z-IKO - NBX6040Z-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nbx6040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number											
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g					
60	---	---	---	---	---	---	NBX 6040Z			538	
Boundary dimensions mm											
F_w	D	D_1	D_2	E	H	l_1	$r_{s \min}$	d_f	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾
60	72	85	86.5	40	17	12	1	60	47 500	64 600	103 000 / 224 000 / 4 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390529
Diam. intérieur	60 mm
Diam. extérieur	72 mm
Épaisseur	40 mm
Conditionnement	1
Norme	Sans norme

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE