

## Roulement à aiguilles NBXI2030-IKO - NBXI2030-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nbxi2030-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Mass (Ref.) g		With dust cover Mass (Ref.) g		Identification Number		d	D	D <sub>1</sub>
	---	---	---	---	NBXI 2030	171			
20	---	---	---	---	NBXI 2030	171	20	37	42

  

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring LRT 202520
D <sub>2</sub>	L	B	H			Radial	Radial		
43	30	20.5	11	9.5	20 000	32 100	60 700	9 000	LRT 202520

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390826
Diam. intérieur	20 mm
Diam. extérieur	37 mm
Épaisseur	30 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE