

Roulement à aiguilles NAXI2530-IKO - NAXI2530-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/naxi2530-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification Number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
25	NAXI 2530	179	—	—	—	—	25	42	47

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring		
D ₂	L	B	H			Radial	Radial			Radial	
48	30	20.5	11	9.5	25	100	20	400	33 600	6 500	LRT 253020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390840
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	42 mm
Diam. extérieur	1.654" inch
Epaisseur	30 mm
Epaisseur	1.181" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE