

Roulement à aiguilles NBXI2530Z-IKO - NBXI2530Z-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nbxi2530z-iko>

UNIDIRECTIONAL TYPE NEEDLE ROLLER BEARINGS

Needle Bearings with Thrust Ball Bearing With Inner Ring
Needle Bearings with Thrust Roller Bearing With Inner Ring

Identification number																		
Mass (Ref.) g			With dust cover			Mass (Ref.) g			Mass (Ref.) g			d						
---			---			---			NBXI 2530Z				200	25				
Boundary dimensions mm						Bore diameter mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assemble					
B	H	I ₁	r	r _{min}	r _{max}	d ₁	d ₂	Radial	Axial	Radial	Axial							
20.5	11	9.5	0.6	0.3	30	30	45	25	100	27	400	40	100	81	000	8	000	LRT

(1) Minimum allowable value of chamfer dimension r. Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBXI series. The outer ring has an oil groove and an oil hole. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390871
Diam. intérieur	25 mm
Diam. extérieur	42 mm
Épaisseur	30 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE