

Roulement à aiguilles NBXI3532-IKO - NBXI3532-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nbxi3532-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

| Shaft dia. mm | Identification Number | | | | | | d | D | D _i | | | | | | | |
|------------------------|-----------------------|-----------------|------------------|------------------|-----------------|------------------|----------------|----|----------------|----------------------|--------|--------|--------|---------|-------|------------|
| | Mass (Ref.) g | With dust cover | Mass (Ref.) g | Mass (Ref.) g | With dust cover | Mass (Ref.) g | | | | | | | | | | |
| 35 | --- | --- | --- | NBXI 3532 | 286 | --- | 35 | 52 | 60 | | | | | | | |
| Boundary dimensions mm | | | | | | | | | | | | | | | | |
| D ₂ | L | B | H | I ₁ | r | d _a | d _s | C | C ₀ | Assembled inner ring | | | | | | |
| 61 | 32 | 20 | 13 | 10 | 0.6 | 0.3 | 40 | 40 | 57 | 39 | 29 400 | 41 700 | 54 100 | 133 000 | 6 000 | LRT 354020 |

Notes:
(*) Minimum allowable value of chamfer dimension r.
(†) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952390949 |
| Diam. intérieur | 35 mm |
| Diam. extérieur | 52 mm |
| Épaisseur | 32 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE