

Roulement à aiguilles NBXI3532Z-IKO - NBXI3532Z-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nbxi3532z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification Number						d	D	D ₁			
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g						
35	---	---	---	---	---	---	35	52	60			
NBXI 3532Z 294												
Boundary dimensions mm			Lead-in chamfer mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 354020			
D ₂	L	B		Radial	Axial	Radial	Axial					
61	32	20	13	10	57	39	29 400	41 700	54 100	133 000	6 000	LRT 354020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390956
Diam. intérieur	35 mm
Diam. extérieur	52 mm
Épaisseur	32 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE