

## Roulement à aiguilles NAXI4032Z-IKO - NAXI4032Z-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/naxi4032z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification Number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
40	<b>NAXI 4032Z 324</b>						40	58	65

  

Boundary dimensions mm				Lead-in chamfer radius mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
D <sub>2</sub>	L	B	H			Radial	Radial		
66.5	32	20	14	9	N	N	N	5 000	LRT 404520

Notes<sup>(2)</sup> Minimum allowable value of chamfer dimension r  
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390970
Diam. intérieur	40 mm
Diam. extérieur	58 mm
Épaisseur	32 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE