

Roulement à aiguilles NBXI4032-IKO - NBXI4032-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nbxi4032-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		d	D	D ₁
	—	—	—	—	—	—			
40	—	—	—	—	NBXI 4032	344	40	58	65

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 404520
D ₂	L	B	H			Radial	Radial		
66.5	32	20	14	9	31 000	40 800	60 200	133 000	5 500

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
 Remark 1: The outer ring has an oil groove and an oil hole.
 2: Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390987
Diam. intérieur	40 mm
Diam. extérieur	58 mm
Épaisseur	32 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE