


Roulement à aiguilles NAXI5040-IKO - NAXI5040-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/naxi5040-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification Number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
50	NAXI 5040	582	—	—	—	—	50	72	85

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 506025					
D ₂	L	B	H		Radial	Axial	Radial	Axial							
86.5	40	25.5	17	12	1	1	60	75	59	47 500	41 400	103 000	89 700	4 000	LRT 506025

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952391045
Diam. intérieur	50 mm
Diam. intérieur	1.969" inch
Diam. extérieur	72 mm
Diam. extérieur	2.835" inch
Epaisseur	40 mm
Epaisseur	1.575" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE