

Roulement à aiguilles NAXI6040Z-IKO - NAXI6040Z-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/naxi6040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

| Shaft dia. mm | Identification Number | | | | | | d | D | D ₁ |
|------------------|-----------------------|-----------------|------------------|------------------|-----------------|------------------|----|----|----------------|
| | Mass (Ref.) g | With dust cover | Mass (Ref.) g | Mass (Ref.) g | With dust cover | Mass (Ref.) g | | | |
| 60 | NAXI 6040Z 801 | | | | | | 60 | 85 | 95 |

| Boundary dimensions mm | | | | Lead-in chamfer mm | Basic dynamic load rating C | Basic static load rating C ₀ | | Allowable rotational speed ⁽¹⁾ rpm | Assembled inner ring LRT 607025 | | | | | |
|---------------------------|----|------|----|-----------------------|--------------------------------|--|--------|--|------------------------------------|--------|---------|---------|-------|--|
| D ₂ | L | B | H | | | Radial | Radial | | | Axial | | | | |
| 96.5 | 40 | 25.5 | 18 | 11 | 1 | 70 | 85 | 68 | 55 500 | 43 100 | 120 000 | 101 000 | 3 500 | |

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remark 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952391090 |
| Diam. intérieur | 60 mm |
| Diam. extérieur | 85 mm |
| Épaisseur | 40 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE