

Rotule GE SB85A-IKO - SB85A-IKO

<https://www.123roulement.com/roulement-palier/rotule/ge/sb85a-iko>

SPHERICAL BUSHINGS
steel Spherical Bushings



| Identification number | Mass (Ref.) | Boundary dimensions mm | | | | | | Per titi c |
|-----------------------|-------------|------------------------|-----|----|----|----------------|------------------------|------------|
| | | d | D | B | C | d _k | r _{s min} (°) | |
| SB 85A | 4.29 | 85 | 135 | 74 | 63 | 125 | 0.6 | |

| Mounting dimensions mm | | | Dynamic load capacity C _d | Static load capacity C _s |
|------------------------|-------|------|--------------------------------------|-------------------------------------|
| Max. (°) | Max. | Min. | | |
| 100.5 | 130.5 | 116 | 772 000 | 4 630 000 |

Minimum allowable value of chamfer dimensions r₁ and r₂
When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value.
The inner ring and the outer ring have an oil groove and two oil holes, respectively.
Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952391465 |
| Diam. intérieur | 85 mm |
| Diam. extérieur | 135 mm |
| Épaisseur | 74 mm |
| Type | GE |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE