


Rotule GE
GE100ES-2RS-IKO - GE100ES-2RS-IKO
<https://www.123roulement.com/roulement-palier/rotule/ge/ge100es-2rs-iko>



SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



GE-ES-2RS

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm							Permissible tilting angle degrees	
	Without seals	With seals		d	D	B	C	d _k	r ₁ (1)	r ₂ (1)	α	α _l
100		GE 100ES-2RS	4.43	100	150	70	55	130	1	1	7	5

Mounting dimensions mm				Dynamic load capacity C _d N	Static load capacity C _s N
d _s	D _s	Min.	Max.		
Min.	Max.(2)	Max.	Min.		
105.5	109.5	144.5	127	701 000	4 210 000

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952391960
Diam. intérieur	100 mm
Diam. extérieur	150 mm
Epaisseur	70 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.com
03 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE