


Galet de roulement CRY24-V-IKO - CRY24-V-IKO

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/galet-roulement/cry24-v-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



Shaft dia. mm (inch)	Identification number		Max (Ref.) g	Boundary dimensions: mm(inch)				Basic dynamic load rating C	Basic static load rating C ₀				
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C						
11.112 ($\frac{7}{16}$)	CRY 24 V		186	11.112 ($\frac{7}{16}$)	38.100 ($1\frac{1}{2}$)	23.813 (0.9375)	22.225 ($\frac{7}{8}$)	N	N				
				Shaft dia.									
				Push fit		Drive fit		Press fit					
				Min.	Max.	Min.	Max.	Min.	Max.				
				28.8 (1.134)	1.588 ($\frac{1}{16}$)	11.095	11.105	11.110	11.120	11.115	11.125	28 200	40 100

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952398112
Diam. intérieur	11.112 mm
Diam. extérieur	38.1 mm
Épaisseur	23.813 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE