


Galet de roulement CRY30-VR-IKO - CRY30-VR-IKO

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/galet-roulement/cry30-vr-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series Full Complement Type/With Inner Ring



| Shaft dia. mm (inch) | Identification number | | Max (Ref.) | Boundary dimensions: mm(inch) | | | | Basic dynamic load rating C | Basic static load rating C ₀ | | | | |
|----------------------------|---------------------------------------|---------------------------------------|---------------|-------------------------------|--------|-----------|--------|-----------------------------------|---|--------|--------|--------|--------|
| | Shield type Cylindrical outer ring | Sealed type Cylindrical outer ring | | g | d | D | B | | | C | | | |
| 12.700 (1/2) | CRY 30 VR | | 363 | 12.700 | 47.625 | 26.988 | 25.400 | | | | | | |
| | | | | Shaft dia. | | | | | | | | | |
| | | | | Push fit | | Drive fit | | Press fit | | | | | |
| | | | | Min. | Max. | Min. | Max. | Min. | Max. | | | | |
| | | | | 32.7(1.287) | 500 | 12.682 | 12.692 | 12.698 | 12.708 | 12.708 | 12.718 | 35 300 | 55 600 |

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952398891 |
| Diam. intérieur | 12.7 mm |
| Diam. intérieur | 1/2" inch |
| Diam. extérieur | 47.625 mm |
| Diam. extérieur | 1 7/8" inch |
| Epaisseur | 26.988 mm |
| Epaisseur | 1 1/16" inch |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE