

## Roulement conique 30228-JR-JTEKT - 30228-JR-KOYO

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/30228-jr-koyo>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>		
d	D	T	B	C	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.					
140	250	45.75	42	36	4	3	420	570	1 500	1 900	30228JR			
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> min.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> max.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
4FB	49.4	158	163	236	219	237	9	9.5	3	2.5	0.44	1.38	0.76	8.97

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952419763
Diam. intérieur	140 mm
Diam. intérieur	5.512" inch
Diam. extérieur	250 mm
Diam. extérieur	9.843" inch
Epaisseur	45.75 mm
Epaisseur	1.801" inch
Poids	8989 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE